



V2K Y2K



V2K Y2K FLUID POWER

2015 PRODUCT CATALOG

Y2K FLUID POWER

About:

Y2K Fluid Power is an original equipment manufacturer (OEM) based in Sioux Falls, South Dakota. We design and manufacture a complete line of filtration and fluid conditioning products used for removing moisture and solid particulate contamination in hydraulic and lubricating oil systems. All of our oil handling equipment works together as a system to provide true contamination control. These products were designed for that purpose. This catalog illustrates some of our solutions.

Contact Us:

Address:

Y2K Corporate Office
3620 North Lewis Ave.
Sioux Falls, SD 57104

Phone/Fax:

P. 1-888-925-8882
F. 1-605-332-0988

Email:

Sales@y2kfluidpower.com

Website:

www.y2kfluidpower.com

Markets We Serve:

- Pulp and Paper, Forest Products
- Power Generation
- Surface, Underground, Precious Metals and Coal Mining
- Food Processing
- Injection Molding
- Oil, Gas and Petroleum Refining
- Chemical Processing
- Agriculture
- U.S. Government, Military
- Construction
- Railroad
- Industrial and Automotive
- Primary Metals
- Steel

TABLE OF CONTENTS

HIGH PERFORMANCE SERIES

D Series Drum Filter Cart.....	3
D Series Filter Cart.....	4
D Series Tandem Filter Cart	5
D Series Platform Cart.....	6
D Series Filterpak.....	7
D Series T-3 Tote	8
D Series Panel Unit	9

ECONOMY SERIES

M Series Drum Filter Cart.....	10
M Series Filter Cart	11
M Series Tandem Filter Cart.....	12
M Series Platform Cart	13
M Series Filterpak	14
M Series T-3 Tote.....	15
M Series Panel Unit.....	16
Ultralight Filterpak.....	17
Y Series Drum Topper	18
D Series Spin-On Filter Elements	19
M Series Spin-On Filter Elements	20
Y Series Spin-On Filter Elements.....	21
Drum Adapter	22
Gearbox Adapter	23
Hydraulic Adapter.....	24
Tote Adapter	25
Magnetic Filtration	26
Particle Monitor.....	27
Fluid Patch Test Kit	28
Parts & Accessories	29
Model Code Builder	30

D SERIES DRUM FILTER CART

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com

Typical Applications:

- Filtering contaminated systems
- Flushing new or repaired systems
- Pre-filtering new oil
- Transferring oils
- Topping off reservoirs
- Collecting oil samples for analysis
- Dispensing new oil

Standard Features:

Materials:

- Frame: Carbon steel with magnetic kickstand
- Paint: Multiple color options available
- Motor: 1HP, 115vac, 60Hz or Pneumatic
- Filter Heads: Medium pressure, cast aluminum heads
- Pump: Heavy duty, cast steel gear pump. Available in 1, 2, 5 and 10 GPM
- Connections: Various quick connect options available
- Hoses: 7ft. Clear PVC, steel reinforced hose or hydraulic hose
- Power Switch: Sealed On/Off Power Switch

Filter Indicators:

- Slide bar indicators trigger at 50psid when elements need to be changed.

Pump Relief:

- Opens at 150psi

Weight:

- Approx. 145lbs (will vary depending on options)

Dimensions:

- Approx. 23"L x 21"W x 59"H

Replacement Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1066	$\beta_{4(c)}=2000$	14/12/9 - 13/11/8
P1065	$\beta_{7(c)}=2000$	18/16/13 - 15/13/10
P1063	$\beta_{10(c)}=1000$	19/17/14 - 18/16/13
P1064	$\beta_{25(c)}=2000$	20/18/15 - 19/17/14
P1048WR	Water Removal	

All D Series elements measure 5" x 14".



D SERIES FILTER CART

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com

Typical Applications:

- Filtering contaminated systems
- Flushing new or repaired systems
- Pre-filtering new oil
- Transferring oils
- Topping off reservoirs
- Collecting oil samples for analysis
- Dispensing new oil

Standard Features:

Materials:

- Frame: Carbon steel with drip pan
- Paint: Multiple color options available
- Motor: 1HP, 115vac, 60Hz or Pneumatic
- Filter Heads: Medium pressure, cast aluminum heads
- Pump: Heavy duty, cast steel gear pump. Available in 1, 2, 5 and 10 GPM
- Connections: Various quick connect options available
- Hoses: 7ft. Clear PVC, steel reinforced hose or hydraulic hose
- Power Switch: Sealed On/Off Power Switch

Filter Indicators:

- Slide bar indicator triggers at 50psid when elements need to be changed.

Pump Relief:

- Opens at 150psi

Weight:

- Approx. 125lbs (will vary depending on options)

Dimensions:

- Approx. 23"L x 22"W x 52"H

Replacement Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1066	$\beta_{4(c)}=2000$	14/12/9 - 13/11/8
P1065	$\beta_{7(c)}=2000$	18/16/13 - 15/13/10
P1063	$\beta_{10(c)}=1000$	19/17/14 - 18/16/13
P1064	$\beta_{25(c)}=2000$	20/18/15 - 19/17/14
P1048WR	Water Removal	

All D Series elements measure 5" x 14".



D SERIES TANDEM FILTER CART

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com



Typical Applications:

- Filtering contaminated systems
- Flushing new or repaired systems
- Pre-filtering new oil
- Transferring oils
- Topping off reservoirs
- Collecting oil samples for analysis
- Dispensing new oil

Standard Features:

Materials:

- Frame: Carbon steel
- Paint: Multiple color options available
- Motor: 1HP, 115vac, 60Hz or Pneumatic
- Filter Heads: Medium pressure, cast aluminum heads
- Pump: Heavy duty, cast steel gear pump. Available in 1, 2, 5 and 10 GPM
- Connections: Various quick connect options available
- Hoses: 7ft. Clear PVC, steel reinforced hose or hydraulic hose
- Power Switch: Sealed On/Off Power Switch

Filter Indicators:

- Slide bar indicator triggers at 50psid when elements need to be changed.

Pump Relief:

- Opens at 150psi

Weight:

- Approx. 200lbs (will vary depending on options)

Dimensions:

- Approx. 23"L x 22"W x 52"H

Replacement Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1066	$\beta_{4(c)}=2000$	14/12/9 - 13/11/8
P1065	$\beta_{7(c)}=2000$	18/16/13 - 15/13/10
P1063	$\beta_{10(c)}=1000$	19/17/14 - 18/16/13
P1064	$\beta_{25(c)}=2000$	20/18/15 - 19/17/14
P1048WR	Water Removal	

All D Series elements measure 5" x 14".

D SERIES PLATFORM CART

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com

Standard Features:

Materials:

- Frame: Carbon steel platform frame with drip pan & utility tray
- Paint: Multiple color options available
- Tank(s): 32, 71 and 115 gallon poly tanks available
- Motor: 1HP, 115vac, 60Hz or Pneumatic
- Filter Heads: Medium pressure, cast aluminum heads
- Pump: Heavy duty, cast steel gear pump. Available in 1, 2, 5 and 10 GPM
- Connections: Various quick connect options available
- Hoses: 7ft. Clear PVC, steel reinforced hose or hydraulic hose
- Power Switch: Sealed On/Off Power Switch

Filter Indicators:

- Slide bar indicator triggers at 50psid when elements need to be changed.

Pump Relief:

- Opens at 150psi

Weight:

- Approx. 250lbs
(will vary depending on options)

Dimensions:

- Approx. 55"L x 24"W x 52"H
(dual tank, dual elements)

Typical Applications:

- Pre-filtering new oil
- Transferring oils
- Topping off reservoirs or containers
- Dispensing new oil
- Waste oil extraction

Replacement Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1066	$\beta_{4(c)}=2000$	14/12/9 - 13/11/8
P1065	$\beta_{7(c)}=2000$	18/16/13 - 15/13/10
P1063	$\beta_{10(c)}=1000$	19/17/14 - 18/16/13
P1064	$\beta_{25(c)}=2000$	20/18/15 - 19/17/14
P1048WR	Water Removal	

All D Series elements measure 5" x 14".



If You Have Questions

- Please feel free to contact our sales team at sales@y2kfluidpower.com or 1-888-925-8882. We will be more than happy to help!

D SERIES FILTERPAK

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com

Standard Features:

Materials:

- Frame: Heavy duty, diamond plated aluminum frame
- Motor: 1/4 HP, 1/2HP or 1HP, 115vac, 60Hz
- Filter Heads: Medium pressure, cast aluminum heads
- Pump: Heavy duty, cast steel gear pump. Available in 1, 2, 5 and 10 GPM
- Connections: Various quick connect options available
- Hoses: 7ft. Clear PVC, steel reinforced hose or hydraulic hose
- Power Switch: Sealed On/Off Power Switch

Filter Indicators:

- Slide bar indicator triggers at 50psid when elements need to be changed.

Pump Relief:

- Opens at 150psi

Weight:

- Approx. 50lbs (will vary depending on options)

Dimensions:

- Approx. 8"L x 16"W x 16"H

Typical Applications:

- Filtering contaminated system
- Flushing new or repaired systems
- Pre-filtering new oil
- Transferring oils
- Topping off reservoirs
- Dispensing new oil


Replacement Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1066	$\beta_{4(c)}=2000$	14/12/9 - 13/11/8
P1065	$\beta_{7(c)}=2000$	18/16/13 - 15/13/10
P1063	$\beta_{10(c)}=1000$	19/17/14 - 18/16/13
P1064	$\beta_{25(c)}=2000$	20/18/15 - 19/17/14
P1048WR	Water Removal	

All D Series elements measure 5" x 14".

Looking For Options?

- Please refer to our model code builder on page 30 for complete customization on any of our Y2K Fluid Power products.



D SERIES T-3 TOTE

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com

Typical Applications:

- Filtering contaminated systems
- Flushing new or repaired systems
- Pre-filtering new oil
- Transferring oils
- Topping off reservoirs or containers
- Dispensing new oil



Standard Features:

Materials:

- Frame: Carbon steel, 30 gallon tank with 4 wheels
- Paint: Multiple color options available
- Motor: 1HP, 115vac, 60Hz or Pneumatic
- Filter Heads: Medium pressure, cast aluminum heads
- Pump: Heavy duty, cast steel gear pump. Available in 1, 2, 5 and 10 GPM
- Connections: Various quick connect options available
- Hoses: 7ft. Clear PVC, steel reinforced hose or hydraulic hose
- Power Switch: Sealed On/Off Power Switch
- Desiccant Breather

Filter Indicators:

- Slide bar indicator triggers at 50psid when elements need to be changed.

Pump Relief:

- Opens at 150psi

Weight:

- Approx. 125lbs (will vary depending on options)

Dimensions:

- Approx. 23"L x 22"W x 52"H

Replacement Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1066	$\beta_{4(c)}=2000$	14/12/9 - 13/11/8
P1065	$\beta_{7(c)}=2000$	18/16/13 - 15/13/10
P1063	$\beta_{10(c)}=1000$	19/17/14 - 18/16/13
P1064	$\beta_{25(c)}=2000$	20/18/15 - 19/17/14
P1048WR	Water Removal	

All D Series elements measure 5" x 14".

D SERIES PANEL UNIT

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com

Typical Applications:

- Filtering contaminated system
- Collecting oil samples for analysis
- Dispensing new oil
- Permanent installations

Standard Features:

Materials:

- Frame: Carbon steel with drip tray
- Paint: Multiple color options available
- Motor: 1HP, 115vac, 60Hz or Pneumatic
- Filter Heads: Medium pressure, cast aluminum heads
- Pump: Heavy duty, cast steel gear pump. Available in 1, 2, 5 and 10 GPM

Filter Indicators:

- Slide bar indicator triggers at 50psid when elements need to be changed.

Pump Relief:

- Opens at 150psi

Weight:

- Approx. 75-80lbs (will vary depending on options)

Dimensions:

- Approx. 24"L x 12"W x 29"H

Replacement Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1066	$\beta_{4(c)}=2000$	14/12/9 - 13/11/8
P1065	$\beta_{7(c)}=2000$	18/16/13 - 15/13/10
P1063	$\beta_{10(c)}=1000$	19/17/14 - 18/16/13
P1064	$\beta_{25(c)}=2000$	20/18/15 - 19/17/14
P1048WR	Water Removal	

All D Series elements measure 5" x 14".



Looking For Options?

- Please refer to our model code builder on page 30 for complete customization on any of our Y2K Fluid Power products.

M SERIES DRUM FILTER CART

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com



Typical Applications:

- Pre-filtering new oil
- Transferring oils
- Topping off reservoirs
- Dispensing new oil

Standard Features:

Materials:

- Frame: Carbon steel with magnetic kickstand
- Paint: Multiple color options available
- Motor: 1HP, 115vac, 60Hz or Pneumatic
- Filter Heads: Low pressure, aluminum heads
- Pump: Aluminum gear pump. Available in 2, 5 and 10 GPM
- Connections: Various quick connect options available
- Hoses: 7ft. Clear PVC, steel reinforced hose or hydraulic hose
- Power Switch: Sealed On/Off Power Switch

Filter Indicators:

- Pop up indicator triggers at 50psid when elements need to be changed.

Pump Relief:

- Opens at 150psi

Weight:

- Approx. 145lbs (will vary depending on options)

Dimensions:

- Approx. 23"L x 21"W x 59"H

Replacement Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1068	$\beta_{3(c)}=1000$	14/12/9 - 13/11/8
P1069	$\beta_{6(c)}=1000$	17/15/12 - 14/12/9
P1070	$\beta_{10(c)}=1000$	18/16/13 - 17/15/12
P1071	$\beta_{25(c)}=1000$	21/19/16 - 20/18/15
P1072WR	Water Removal	

All M Series elements measure 5" x 10".

M SERIES FILTER CART

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com



Typical Applications:

- Filtering contaminated system
- Flushing new or repaired systems
- Pre-filtering new oil
- Transferring oils
- Topping off reservoirs
- Collecting oil samples for analysis
- Dispensing new oil

Standard Features:

Materials:

- Frame: Carbon steel with drip pan
- Paint: Multiple color options available
- Motor: 1HP, 115vac, 60Hz or Pneumatic
- Filter Heads: Low pressure, aluminum heads
- Pump: Aluminum gear pump. Available in 2, 5 and 10 GPM
- Connections: Various quick connect options available
- Hoses: 7ft. Clear PVC, steel reinforced hose or hydraulic hose
- Power Switch: Sealed On/Off Power Switch

Filter Indicators:

- Pop up indicator triggers at 50psid when elements need to be changed.

Pump Relief:

- Opens at 150psi

Weight:

- Approx. 125lbs (will vary depending on options)

Dimensions:

- Approx. 23"L x 22"W x 52"H

Replacement Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1068	$\beta_{3(c)}=1000$	14/12/9 - 13/11/8
P1069	$\beta_{6(c)}=1000$	17/15/12 - 14/12/9
P1070	$\beta_{10(c)}=1000$	18/16/13 - 17/15/12
P1071	$\beta_{25(c)}=1000$	21/19/16 - 20/18/15
P1072WR	Water Removal	

All M Series elements measure 5" x 10".

M SERIES TANDEM FILTER CART

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com



Typical Applications:

- Filtering contaminated systems
- Flushing new or repaired systems
- Pre-filtering new oil
- Transferring oils
- Topping off reservoirs
- Collecting oil samples for analysis
- Dispensing new oil

Standard Features:

Materials:

- Frame: Carbon steel
- Paint: Multiple color options available
- Motor: 1HP, 115vac, 60Hz or Pneumatic
- Filter Heads: Low pressure, aluminum heads
- Pump: Aluminum gear pump. Available in 2, 5 and 10 GPM
- Connections: Various quick connect options available
- Hoses: 7ft. Clear PVC, steel reinforced hose or hydraulic hose
- Power Switch: Sealed On/Off Power Switch

Filter Indicators:

- Pop up indicator triggers at 50psid when elements need to be changed.

Pump Relief:

- Opens at 150psi

Weight:

- Approx. 200lbs (will vary depending on options)

Dimensions:

- Approx. 23"L x 22"W x 52"H

Replacement Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1068	β3(c)=1000	14/12/9 - 13/11/8
P1069	β6(c)=1000	17/15/12 - 14/12/9
P1070	β10(c)=1000	18/16/13 - 17/15/12
P1071	β25(c)=1000	21/19/16 - 20/18/15
P1072WR	Water Removal	

All M Series elements measure 5" x 10".

M SERIES PLATFORM CART

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com

Standard Features:

Materials:

- Frame: Carbon steel platform frame with drip pan & utility tray
- Paint: Multiple color options available
- Tank(s): 32, 71 and 115 gallon poly tanks available
- Motor: 1HP, 115vac, 60Hz or Pneumatic
- Filter Heads: Low pressure, aluminum heads
- Pump: Aluminum gear pump. Available in 2, 5 and 10 GPM
- Connections: Various quick connect options available
- Hoses: 7ft. Clear PVC, steel reinforced hose or hydraulic hose
- Power Switch: Sealed On/Off Power Switch

Filter Indicators:

- Pop up indicator triggers at 50psid when elements need to be changed.

Pump Relief:

- Opens at 150psi

Weight:

- Approx. 250lbs (will vary depending on options)

Dimensions:

- Approx. 55"L x 24"W x 52"H (dual tank, dual elements)

Typical Applications:

- Pre-filtering new oil
- Transferring oils
- Topping off reservoirs or containers
- Dispensing new oil

Replacement Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1068	$\beta_{3(c)}=1000$	14/12/9 - 13/11/8
P1069	$\beta_{6(c)}=1000$	17/15/12 - 14/12/9
P1070	$\beta_{10(c)}=1000$	18/16/13 - 17/15/12
P1071	$\beta_{25(c)}=1000$	21/19/16 - 20/18/15
P1072WR	Water Removal	

All M Series elements measure 5" x 10".



Looking For Options?

- Please refer to our model code builder on page 30 for complete customization on any of our Y2K Fluid Power products.

M SERIES FILTERPAK

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com

Typical Applications:

- Filtering contaminated systems
- Flushing new or repaired systems
- Pre-filtering new oil
- Transferring oils
- Topping off reservoirs
- Dispensing new oil



Standard Features:

Materials:

- Frame: Heavy duty, diamond plated aluminum frame
- Motor: 1/4 HP, 1/2HP or 1HP, 115vac, 60Hz
- Filter Heads: Low pressure, aluminum heads
- Pump: Aluminum gear pump. Available in 2, 5 and 10 GPM
- Connections: Various quick connect options available
- Hoses: 7ft. Clear PVC, steel reinforced hose or hydraulic hose
- Power Switch: Sealed On/Off Power Switch

Filter Indicators:

- Pop up indicator triggers at 50psid when elements need to be changed.

Pump Relief:

- Opens at 150psi

Weight:

- Approx. 50lbs (will vary depending on options)

Dimensions:

- Approx. 8"L x 16"W x 16"H

Replacement Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1068	$\beta_{3(c)}=1000$	14/12/9 - 13/11/8
P1069	$\beta_{6(c)}=1000$	17/15/12 - 14/12/9
P1070	$\beta_{10(c)}=1000$	18/16/13 - 17/15/12
P1071	$\beta_{25(c)}=1000$	21/19/16 - 20/18/15
P1072WR	Water Removal	


All M Series elements measure 5" x 10".

M SERIES T-3 TOTE

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com

Typical Applications:

- Filtering contaminated systems
- Flushing new or repaired systems
- Pre-filtering new oil
- Transferring oils
- Topping off reservoirs or containers
- Dispensing new oil



Standard Features:

Materials:

- Frame: Carbon steel, 30 gallon tank with 4 wheels
- Paint: Multiple color options available
- Motor: 1HP, 115vac, 60Hz or Pneumatic
- Filter Heads: Low pressure, aluminum heads
- Pump: Aluminum gear pump. Available in 2, 5 and 10 GPM
- Connections: Various quick connect options available
- Hoses: 7ft. Clear PVC, steel reinforced hose or hydraulic hose
- Power Switch: Sealed On/Off Power Switch
- Desiccant Breather included

Filter Indicators:

- Pop up indicator triggers at 50psid when elements need to be changed.

Pump Relief:

- Opens at 150psi

Weight:

- Approx. 125lbs (will vary depending on options)

Dimensions:

- Approx. 31"L x 23"W x 47"H

Replacement Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1068	$\beta_{3(c)}=1000$	14/12/9 - 13/11/8
P1069	$\beta_{6(c)}=1000$	17/15/12 - 14/12/9
P1070	$\beta_{10(c)}=1000$	18/16/13 - 17/15/12
P1071	$\beta_{25(c)}=1000$	21/19/16 - 20/18/15
P1072WR	Water Removal	


All M Series elements measure 5" x 10".

M SERIES PANEL UNIT

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com

Typical Applications:

- Filtering contaminated systems
- Collecting oil samples for analysis
- Dispensing new oil



Standard Features:

Materials:

- Frame: Carbon steel with drip tray
- Paint: Multiple color options available
- Motor: 1HP, 115vac, 60Hz or Pneumatic
- Filter Heads: Low pressure, aluminum heads
- Pump: Aluminum gear pump. Available in 2, 5 and 10 GPM
- **Filter Indicators:**
- Pop up indicator triggers at 50psid when elements need to be changed.

Pump Relief:

- Opens at 150psi

Weight:

- Approx. 75-80lbs (will vary depending on options)

Dimensions:

- Approx. 24"L x 12"W x 18"H

Replacement Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1068	$\beta_{3(c)}=1000$	14/12/9 - 13/11/8
P1069	$\beta_{6(c)}=1000$	17/15/12 - 14/12/9
P1070	$\beta_{10(c)}=1000$	18/16/13 - 17/15/12
P1071	$\beta_{25(c)}=1000$	21/19/16 - 20/18/15
P1072WR	Water Removal	

All M Series elements measure 5" x 10".

ULTRALIGHT FILTERPAK

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com

Typical Applications:

- Filtering contaminated systems
- Flushing new or repaired systems
- Pre-filtering new oil
- Transferring oils
- Topping off reservoirs or containers
- Dispensing new oil



Standard Features:

Materials:

- Frame: Heavy duty, diamond plated aluminum frame
- Motor: 1/4HP, 115vac, 60Hz
- Filter Heads: Low pressure, aluminum heads
- Pump: Aluminum gear pump. Available in 1, 2 and 5 GPM
- Connections: Various quick connect options available
- Hoses: 7ft. Clear PVC, steel reinforced hose or hydraulic hose
- Power Switch: Sealed On/Off Power Switch

Filter Indicators:

- Pop up indicator triggers at 36psid when elements need to be changed.

Pump Relief:

- Opens at 65psi

Weight:

- Approx. 35lbs (will vary depending on options)

Dimensions:

- Approx. 14"L x 8"W x 15"H

Replacement Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1068	$\beta_{3(c)}=1000$	14/12/9 - 13/11/8
P1069	$\beta_{6(c)}=1000$	17/15/12 - 14/12/9
P1070	$\beta_{10(c)}=1000$	18/16/13 - 17/15/12
P1071	$\beta_{25(c)}=1000$	21/19/16 - 20/18/15
P1072WR	Water Removal	

All M Series elements measure 5" x 10".

Y SERIES DRUM TOPPER

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com

Typical Applications:

- Pre-filtering new oil
- Transferring oils
- Topping off reservoirs or containers
- Dispensing new oil



Standard Features:

Materials:

- Frame: Heavy duty steel frame
- Paint: Multiple color options available
- Motor: 1/4HP, 115vac, 60Hz
- Filter Heads: Low pressure, aluminum heads
- Pump: Heavy duty, steel gear pump. Available in 1, 2 and 5 GPM
- Connections: Various quick connect options available
- Hoses: 7ft. Clear PVC, steel reinforced hose or hydraulic hose
- Power Switch: Sealed On/Off Power Switch

Filter Indicators:

- Pop-up indicator triggers at 25psid when elements need to be changed.

Pump Relief:

- Opens at 65psi

Weight:

- Approx. 38lbs (will vary depending on options)

Dimensions:

- Approx. 20"L x 12"W x 15"H

Replacement Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P10071	$\beta_{3(c)}=1000$	14/12/9 - 13/11/8
P1007	$\beta_{5(c)}=1000$	15/13/10 - 14/12/9
P1011	$\beta_{7(c)}=1000$	17/15/12 - 15/13/10
P1024	$\beta_{12(c)}=1000$	19/17/14 - 17/15/12
P1010	$\beta_{22(c)}=1000$	21/19/16 - 19/17/14
P1008L	Water Removal	
P1008	Water Removal	

All Y Series elements measure 3" x 8" except the P1008, it measures 3" x 4".

D SERIES SPIN-ON FILTER ELEMENT

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com



When your system demands the ultimate in fluid cleanliness, our D Series Spin-On Filter Elements are an important line of defense in maintaining fluid quality. These single-pass filter elements can help you save on costly component replacement and minimize equipment downtime. They are available in various micron and water removal sizes to fit your needs.

Benefits:

- Proprietary filter media design ensures superior dirt retention over other elements
- Internal O-ring gasket eliminates leakage
- Viton seals offer the widest chemical compatibility

Standard Features:

- Max working pressure of 350 PSI
- Burst pressure of 800 PSI
- Thread size 1 3/4" - 12
- Operating temperature of -40-190F
- Compatible with all of the D series filtration products

Filter Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1066	$\beta_{4(c)}=2000$	14/12/9 - 13/11/8
P1065	$\beta_{7(c)}=2000$	18/16/13 - 15/13/10
P1063	$\beta_{10(c)}=1000$	19/17/14 - 18/16/13
P1064	$\beta_{25(c)}=2000$	20/18/15 - 19/17/14
P1048WR	Water Removal	

All D Series elements measure 5" x 14".

M SERIES SPIN-ON FILTER ELEMENTS

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com



Our M-Series Spin-On Filter Elements are an important line of defense in maintaining fluid quality. These filter elements have a wide range of chemical compatibility, which allows them to be used in most of your industrial applications. They are available in multiple micron and water removal sizes to accommodate your needs.

Benefits:

- Synthetic microfiber media offers a wide range of chemical compatibility
- Minimal pressure drop across a wide range of viscosities
- Universal connection makes it easily adaptable and equivalent to many OEM filters

Standard Features:

- Max working pressure of 174 PSI
- Thread size 1 1/2" - 16UN
- Operating temperature of -25F to 230F
- Compatible with all of the M Series filtration products

Filter Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1068	β3(c)=1000	14/12/9 - 13/11/8
P1069	β6(c)=1000	17/15/12 - 14/12/9
P1070	β10(c)=1000	18/16/13 - 17/15/12
P1071	β25(c)=1000	21/19/16 - 20/18/15
P1072WR	Water Removal	

All M Series elements measure 5" x 10".

Y SERIES SPIN-ON FILTER ELEMENT

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com



Our Y-Series Spin-On Filter Elements are an economical and cost effective spin-on element. Available in a wide range of micron and water removal ratings, these filter elements will fit most of your needs. They also offer a wide range of chemical and thermal compatibility, making them ideal for most industrial applications.

Benefits:

- Synthetic microglass media offers a wide range of chemical compatibility
- Variety of filtration efficiencies to meet your system requirements
- Compact size, makes these an economical spin-on option

Standard Features:

- Max working pressure of 250 PSI
- Thread size 1 1/2" - 16UN
- Compatible with mineral and most synthetic oils
- Compatible with the Drum Topper and other filtration products

Filter Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P10071	$\beta_{3(c)}=1000$	14/12/9 - 13/11/8
P1007	$\beta_{5(c)}=1000$	15/13/10 - 14/12/9
P1011	$\beta_{7(c)}=1000$	17/15/12 - 15/13/10
P1024	$\beta_{12(c)}=1000$	19/17/14 - 17/15/12
P1010	$\beta_{22(c)}=1000$	21/19/16 - 19/17/14
P1008L	Water Removal	
P1008	Water Removal	

All Y Series elements measure 3" x 8" except the P1008, it measures 3" x 4".

DRUM ADAPTER KIT

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com



The Drum Adapter Kit helps keep your stored lubricants free of moisture and particulate contamination while in storage or during the fluid transfer process. It also easily allows you to pre-filter your lubricant, ensuring you're only putting clean, dry oil into your equipment.

Benefits:

- Easily modify your equipment for a seamless connection to various filtration systems
- Prevents the ingress of dirt and moisture by utilizing a desiccant breather
- Customizable to fit all your needs

Standard Features:

- Various quick disconnects with steel dust plugs allow for various configurations
- 2" NPT connection easily replaces standard drum bungs
- Replaceable desiccant breather

Looking For Options?

- Please refer to our model code builder on page 30 for complete customization on any of our Y2K Fluid Power products.

GEARBOX ADAPTER KIT

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com



Our Gearbox Adapter Kit allows you to easily adapt your equipment with a desiccant breather and quick connects with the use of a 3/4" NPT threaded adapter. This allows your system to remain completely sealed to atmospheric ingress, while allowing for easy access during offline filtration or topping reservoirs off.

Benefits:

- Easily modify your equipment for a seamless connection to various filtration systems
- Prevents the ingress of dirt and moisture by utilizing a desiccant breather
- Customizable to fit all your needs

Standard Features:

- Various quick disconnects with steel dust plugs
- Adapter with 3/4" NPT connection easily adapts to most gearboxes
- Replaceable desiccant breather
- Customizable to fit your specific needs

Looking For Options?

- Please refer to our model code builder on page 30 for complete customization on any of our Y2K Fluid Power products.

HYDRAULIC ADAPTER KIT

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com



Our Hydraulic Adapter Kit allows you to easily adapt your equipment with a desiccant breather and quick connects with the use of a 6-hole adapter. This allows your system to remain completely sealed to atmospheric ingress, while allowing for easy access during offline filtration or topping reservoirs off.

Benefits:

- Easily modify your equipment for a seamless connection to various filtration systems
- Prevents the ingress of dirt and moisture by utilizing a desiccant breather
- Customizable to fit all your needs

Standard Features:

- Various quick disconnects with steel dust plugs
- 6 bolt adapter fits most OEM connections
- Replaceable desiccant breather
- Customizable to fit your specific needs

If You Have Questions...

- Please feel free to contact our sales team at sales@y2kfluidpower.com or 1-888-925-8882. We will be more than happy to help!

TOTE ADAPTER KIT

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com

**TB-1004-1
(Includes Both)**



**TB-1004-2
(Includes
Suction Out
Only)**

*Tube lengths available
in various sizes.*

Our Tote Adapter Kit allows you to easily adapt your equipment with a desiccant breather and quick connects with the use of a 2" NPT threaded adapter. This allows your system to remain completely sealed to atmospheric ingress, while allowing for easy access during offline filtration or topping reservoirs off.

Benefits:

- Easily modify your equipment for a seamless connection to various filtration systems
- Prevents the ingress of dirt and moisture by utilizing a desiccant breather
- Customizable to fit all your needs

Standard Features:

- Various quick disconnects with steel dust plugs
- 2" NPT connection easily connects to most poly totes
- Replaceable desiccant breather
- Customizable to fit your specific needs
- Spring loaded faucet for easy dispensing

Looking For Options?

- Please refer to our model code builder on page 30 for complete customization on any of our Y2K Fluid Power products.

MAGNETIC FILTRATION

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com


Y2K's Magnetic filters, designed with removable rare earth magnetic cores, can capture ferrous contaminants in fluid systems down to $< 1\mu\text{M}$. These pre-filters are an excellent diagnostic tool for contamination monitoring and proactive maintenance. By simply removing the magnetic core and examining the material collected, reliability and maintenance engineers across many industries now have a valuable tool for identifying potential wear related issue before they become catastrophic failures.

Benefits:

- Conveniently identify wear related problems before they become a problem
- Improve filter performance
- Minimize unscheduled downtime
- Extend equipment life
- Extend drain intervals by helping extend oil life

Standard Features:

- **Magnetic Plugs:** Replacement drain or level plugs for a wide range of on-road, off-road and industrial applications
- **Magnetic Rods:** For installation inside our element housing, hydraulic reservoirs, gearboxes and mobile equipment.
- **Magnetic Sticks:** Can be used directly on the outside of all of our spin-on elements.
- **Magnetic Filters:** Can be used as a pre-filter with no flow restriction.



PARTICLE MONITOR

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com

The Particle Monitor is a stationary measurement unit for the continuous monitoring of the particulate contamination in hydraulic and lubricating oil systems. It is designed for connection to low or high pressure hydraulic and lubrication lines from which a small flow of oil (between 300 ml/min and 300 ml/min) is delivered for measurement purposes. The Particle Monitor is suitable for pressure ranges of 0-4,350 PSI (0-300 bar) and oil viscosities up to 4,365 SUS (1,000 cSt). Particulate contamination is detected using an optical measurement cell (laser light). Measurement results in an output shown as a contamination code according to ISO 4406 (1999E) or SAE AS 4059 (D) cleanliness codes reported: >4um (c) >6um (c) >14um (c).

All models feature an analog electric output and an RS-485 interface for outputting the measured contamination levels. The monitor is mounted on a manifold block with an adjustable, pressure compensated flow control valve, externally adjustable. To protect the monitor from any damaging contamination, there is an upstream in-line mesh strainer installed before the inlet port to help eliminate large particles from entering the monitor. This is a serviceable item that should be cleaned and/or replaced if needed. *All applications for the Particle Monitor must be approved by Y2K. Please contact us at 1 (888) 925-8882.*

Particle Monitor
pictured on Custom
Tandem Filter Cart



FLUID PATCH TEST KIT

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com

The Y2K Fluid Patch Test Kit allows you to take a quick snapshot of what's happening inside your equipment. You'll quickly and conveniently be able to conduct on-site particulate analysis in as little as ten minutes. When you need results now and can't wait for an off-site lab, look no further than our convenient all-in-one patch test kit.

Includes:

- Sturdy, watertight Pelican case
- Solvent dispensing bottle with filter
- Vacuum pump
- 100x and 400x microscope
- Camera
- 5UM and .8UM patches
- Pen light
- Software

Benefits:

- Quickly identify opportunities for optimizing filtration performance
- Use it to quickly check and monitor system cleanliness levels
- Optimize drain intervals
- Minimize downtime by identifying minor problems
- Extend equipment life

If You Have Questions...

- Please feel free to contact our sales team at sales@y2kfluidpower.com or 1-888-925-8882. We will be more than happy to help!



Motors

- 1HP, 115VAC, 60HZ, Single Phase; 50HZ motors are available upon request.
- 3 Phase, wash down, severe duty motors
- Explosion Proof, Single and 3 Phase
- DC Motor; 12, 24, 48, 90, 180 VDC
- Air Driven Motor
- Air/Oil Diaphragm; recommended for oil transfer only
- Electronic Variable Flow; Available in three sizes: 5, 10, and 20 GPM

Pumps

- 1, 2, 5, and 10 GPM options are available.
**D and M Series use different pumps.*

Oil Sample Port

- Push Button Sample Ports
- Standard Minimesse Sample Ports
- Standard Minimesse Probe Adapter; connects to the Standard Minimesse
- Standard Minimesse Probe Adapter with Oil Tube Fitting; connects to the Standard Minimesse

Y Strainer

- 149UM Suction Y Strainer; other options are available

Pressure Switch

- Designed to automatically shut off your system when the differential pressure is reached across the filter elements
**Only available on select models*

Pressure Gauges

- Differential Pressure Gauge; 0-30 PSI or 0-60 PSI
- Liquid Filled Pressure Gauge; 0-160 PSI

Quick Disconnects & Dust Caps/Plugs

- ISO A Male Quick Disconnects; available in sizes ½", ¾", and 1"
- ISO B Male Quick Disconnects; available in sizes ½", ¾", and 1"
- Flush Face Male Quick Disconnects; available in sizes ½", ¾", and 1"
- ISO A Female Quick Disconnects; available in sizes ½", ¾", and 1"
- ISO B Female Quick Disconnects; available in sizes ½", ¾", and 1"
- Flush Face Female Quick Disconnects; available in sizes ½", ¾", and 1"
- **All Quick Disconnects come complete with Steel Dust Caps.*

Hose Assemblies

- 1", ¾", and ½" Clear PVC, Steel reinforced Suction Hose Assemblies; available in 7ft, 10ft, and 12ft options
- 1", ¾", and ½" Clear PVC, Steel reinforced Discharge Hose Assemblies; available in 7ft, 10ft, 12ft options

Hose Wand Kit

- 2 ea - 24" Stainless steel hose wands with your choice of an assortment of quick disconnects.
**PVC wands are also available*

By-Pass Valve

- Manual Bypass Valve to bypass filters; includes fittings and ball valve.
**Additional options are available*

Cord Reel

- Retractable, 40ft cord reel with molded plug

MODEL CODE BUILDER

Don't see the options you need?
Contact Y2K at 1(888) 925-8882
or sales@y2kfluidpower.com

EXAMPLE CONFIGURATION:

HT	D5	25	10	5	SH	SQ	40R	2	--	S
Frame Style	Filter Head	Primary Filter	Secondary Filter	Power Source/Pump	Hoses	Hose Connections	Power Cord	Frame Color		Additional Options

For other options not listed above or custom builds, contact Y2K at 888-925-8882 or sales@y2kfluidpower.com

FRAME STYLE

DC	Drum Filter Cart
DT	Drum Topper (Uses the Y series head)
FPA	Aluminum Diamond Plated, FilterPak (Single D series head)
UFPFA	Ultra-light, Aluminum Framed FilterPak (Single M series head)
HT	Filter Cart
PU	Panel Unit
T3	30 Gallon, Steel Tote Cart
TH	Tandem Filter Cart
PT32	Platform Cart w/ 32 gal Poly Tank
PT3232	Platform Cart w/ 2 ea 32 gal Poly Tanks
PT71	Platform Cart w/ 71 gal Poly Tank
PT115	Platform Cart w/ 115 gal Poly Tank
ZC	Special Filter Cart Construction

FILTER HEAD OPTION

Y	Compact, Low Pressure, Aluminum Heads
D5	Medium Pressure, Cast Aluminum Heads
M	Low Pressure, Aluminum Heads
NF	No Heads
ZF	Special Heads

PRIMARY FILTER ELEMENT (1ST STAGE)

Y Series Filters (Only used with the Drum Topper)

3	3"x 8", 3 Micron Filter Element, β3=1000
5	3"x 8", 5 Micron Filter Element, β7=1000
7	3"x 8", 7 Micron Filter Element, β7=1000
12	3"x 8", 12 Micron Filter Element, β12=1000
22	3"x 8", 22 Micron Filter Element, β22=1000
WR	3"x 8", Water Removal Element
WR	3"x 5", Water Removal Element
NE	No Element

M Series Filters (Only used with the M series Heads)

3	5"x 10", 3 Micron Filter Element, β3=1000
6	5"x 10", 6 Micron Filter Element, β6=1000
10	5"x 10", 10 Micron Filter Element, β10=1000
25	5"x 10", 25 Micron Filter Element, β25=1000
WR	5"x 10", Water Removal Element
NE	No Element

D Series Filters (Only used with the D series Heads)

4	5"x 14", 4 Micron Filter Element, β4=2000
7	5"x 14", 7 Micron Filter Element, β7=2000
10	5"x 14", 10 Micron Filter Element, β10=1000
25	5"x 14", 25 Micron Filter Element, β25=2000
WR	5"x 14", Water Removal Element
NE	No Element

SECONDARY FILTER ELEMENT (2ND STAGE)

Y Series Filters (Only used with the Drum Topper)

3	3"x 8", 3 Micron Filter Element, β3=1000
5	3"x 8", 5 Micron Filter Element, β7=1000
7	3"x 8", 7 Micron Filter Element, β7=1000
12	3"x 8", 12 Micron Filter Element, β12=1000
22	3"x 8", 22 Micron Filter Element, β22=1000
WR	3"x 8", Water Removal Element
WR	3"x 5", Water Removal Element
NE	No Element

M Series Filters (Only used with the M series Heads)

3	5"x 10", 3 Micron Filter Element, β3=1000
6	5"x 10", 6 Micron Filter Element, β6=1000
10	5"x 10", 10 Micron Filter Element, β10=1000
25	5"x 10", 25 Micron Filter Element, β25=1000
WR	5"x 10", Water Removal Element
NE	No Element

D Series Filters (Only used with the D series Heads)

4	5"x 14", 4 Micron Filter Element, β4=2000
7	5"x 14", 7 Micron Filter Element, β7=2000
10	5"x 14", 10 Micron Filter Element, β10=1000
25	5"x 14", 25 Micron Filter Element, β25=2000
WR	5"x 14", Water Removal Element
NE	No Element

POWER SOURCE/PUMP

First select the power source required and then your desired pump. ** The 115v, 1HP option is standard and no power source select is needed.

NP	No Power Source
-	115v, 60Hz, 1HP**
C	115v, 60Hz, 1/2 HP
Q	115v, 60Hz, 1/4 HP (Only available on the FilterPak and Drum Topper Units)
E	Explosion Proof (Available in 115v and 230v)
T	Three Phase, 230/460v
M	Air Motor (Filter, Lubricator & Regulator included)
V	Variable Speed
ZP	Special Power Source
1	1 GPM
2	2 GPM
5	5 GPM
10	10 GPM
ZX	Special Pump Option

HOSES

NH	No Hoses
SH	7ft clear, PVC Hose (3/4" Suction & 1/2" Discharge)
SH1	7ft clear, PVC Hose (1" Suction & 3/4" Discharge)
WH	7ft Black Hydraulic Hose (3/4" Suction & 1/2" Discharge)
WH1	7ft Black Hydraulic Hose (1" Suction & 3/4" Discharge)
ZH	Special Hose Type and/or Length

HOSE END CONNECTIONS

CQ	CamLock Connectors
TE	Threaded Ends
SQ	3/4" & 1/2" ISO B Quick Disconnects w/ Steel Dust Plugs
SQ1	1" & 3/4" ISO B Quick Disconnects w/ Steel Dust Plugs
AQ	3/4" & 1/2" ISO A Quick Disconnects w/ Steel Dust Plugs
AQ1	1" & 3/4" ISO A Quick Disconnects w/ Steel Dust Plugs
FQ	3/4" & 1/2" Flush Face Quick Disconnects w/ Steel Dust Plugs
FQ1	1" & 3/4" Flush Face Quick Disconnects w/ Steel Dust Plugs
HW	Hose Wands
NQ	No Connections
ZQ	Special Connections

ELECTRIC CORD

NC	No Cord
4P	4ft Electric Cord
8P	8ft Electric Cord
40R	40ft Retractable Cord Reel
25C	25ft Electric Cord
ZW	Special Cord Type or Plug

FRAME COLOR OPTIONS

1	Blaze Orange
2	Red
3	Blue
4	Black
5	Yellow
6	Silver
7	Special Color

OPTIONS

A	High Oil Temperature Alarm
B	Manual Bypass Valve
D	Digital Flow Meter/Totalizer
E	Color Coded Delta P Gauge
F	Visual Flow Meter
L	Lift Lugs
MF	Magnetic Pre-Filter w/ Cleanable Rod
HE	Heat Exchanger (Air/Oil or Water/Oil)
N	Push Button Sample Ports
O	Standard Minimes Sample Ports
P	Inline Particle Counter
S	Y-Strainer (149 mesh)
T	On/Off Timer Control
W	Water Content Monitor (For use with the Particle Counter)
Y	Yellow Light Filter Indicator
SR	Solid Rubber Tires
FF	No Flat, 13" Tires
Z	Special Features and/or other Options not listed



**3620 North Lewis Ave.
Sioux Falls, SD 57104**

LIMITED WARRANTY

Y2K FLUID POWER warrants to Customer that the product(s) sold by Y2K FLUID POWER shall be free from defects in material and workmanship for a period not to exceed the earlier of one (1) year from date of manufacture or the expiration of the Manufacturer's warranty with respect to any goods in which Y2K FLUID POWER products are installed. The foregoing limited warranty is exclusive; Y2K FLUID POWER makes no implied warranty of merchantability or implied warranty of fitness for any particular purpose, and no other warranties, expressed or implied, concerning its products. Y2K FLUID POWER'S limited warranty hereunder cannot be modified by any person or entity, including, without limitation, any distributor or retailer of Y2K FLUID POWER products. The obligation of Y2K FLUID POWER under this Limited Warranty is limited to the repair or replacement of defective product(s) for which Y2K FLUID POWER issued a RGA number, at Y2K FLUID POWER'S option, upon Customer's return of such product (s) to Y2K FLUID POWER facility, freight prepaid. Y2K FLUID POWER'S obligation to repair or replace defective product(s) hereunder shall arise only if (a) Y2K FLUID POWER technician determines by inspection that such product(s) are defective in material or workmanship, (b) Y2K FLUID POWER has received written notification from the Customer of the defect within the warranted time period and (c) Customer has notified Y2K FLUID POWER in writing of the defect immediately upon discovery thereof. This limited warranty further shall not apply to any product which has been repaired or altered in any way by any person or entity other than Y2K FLUID POWER, nor shall it apply to any product which has been subject to misuse, improper operating conditions, faulty installations, negligence or accidents. All products serviced for free or goodwill, but not warranted, will have a 60-day warranty that covers assembly only. The 60-days will begin on the date serviced at Y2K FLUID POWER.

Limitation of Liability

Except as otherwise agreed herein, Y2K FLUID POWER shall not be liable for special, incidental or consequential damages arising out of the use of, or inability to use, any products sold by Y2K FLUID POWER, including, without limitation, damage or loss of other property or equipment, loss of profits or revenue, or claims of customers for any such damage or loss. The remedies of Customer set forth herein are exclusive, and the liability of Y2K FLUID POWER with respect to any contract, or anything done in connection therewith, such as the performance or breach thereof, or for the manufacture, sale delivery, resale, installation or technical direction or installation, repair or use of any product sold by Y2K FLUID POWER, whether in contract, in tort, under any warranty or otherwise, shall not, except as expressly provided herein, exceed the price of the product(s) or part(s) upon which such liability is based. The price for the product(s) sold by Y2K FLUID POWER is the consideration given by Y2K FLUID POWER in limiting its liability hereunder.



Y2K-CAT-01-15



3620 North Lewis Ave., Sioux Falls, SD 57104 | 888.925.8882 | y2kfluidpower.com