

Desiccant Breathers

D-Series

A large part of contamination control is filtration and reducing ingress. These breathers will filter particulate, humidity and moisture from the air before it reaches the oil.

MODEL	Dia X Height	CFM	GPM	RATING	CONNECTION
D100	5" X 3.5"	35	262	2UM	1" PUSH FIT
D101	5" X 5"	35	262	2UM	1" PUSH FIT
D102	5" X 8"	35	262	2UM	1" PUSH FIT
D103	5" X 8"	35	262	2UM	1" MALE NPT
D104	5" X 8"	35	262	2UM	1" MALE NPT



X-Series

X-Series breathers are excellent for high humidity applications and outdoor applications. These desiccant breathers have check valves on the inlet and exhaust, which only allow air to come into contact with the desiccant when there is a need. They extend the life of the breather and the equipment they are used on. They also have replaceable cartridges.



MODEL	Dia X Height	CFM	GPM	RATING	CONNECTION
X100	3.25" X 6.25"	35	262	2UM	1/2" FNPT
X101	5" X 7"	35	262	2UM	1" PUSH FIT
X102	5" X 10"	35	262	2UM	1" PUSH FIT
X103	5" X 7"	35	262	2UM	1" MALE NPT
X121	5" X 7"	35	262	2UM	2" MALE NPT

*Other types are available for high vibration and high humidity; fume control and more.

