

# Portable Totes



## Innovation and Reliability ALL-In-One!



Model # PT3232YWR3V5SHSQ25C

Getting oils from bulk oil storage and out into the plant is made easy with these portable totes. All oils dispensed from the portable tanks through on-board filters and even include a desiccant or absolute rated air filter.



Carts have a tray for storing and hauling oil containers or other supplies



These units can have two 32 gallon tanks and two pumps and motors. Typically they are set up to bring new oil out into the plant and used oil back (separate tanks and pumps). They are also set up for bringing two different oils out into a plant. They are built in-house, so we can customize them to suit nearly any application.





The Portable Oil Rack and Tool box are optional Equipment that makes storage of essential equipment and supplies. Also available without filters for waste oil collecting.



# Portable Totes

Standard Model Codes:

Example #ST-70-V5-0-0/6/10/11

- PT Portable Tote (Includes Cart with 4 Pneumatic Wheels)
- 32 32 Gallon poly Reservoir
- 71 71 Gallon Poly Reservoir
- V5 0 to 5GPM Variable Speed Drive (115VAC, on/off switch and potentiometer speed control)
- V10 0 to 10GPM Variable Speed Drive (115VAC, on/off switch and potentiometer speed control)
- F1 1GPM Fixed Volume (115VAC, on/off switch)
- F2 2.5GPM Fixed Volume (115VAC, on/off switch)
- F5 5GPM Fixed Volume (115VAC, on/off switch)
- F10 10GPM Fixed Volume (115VAC, on/off switch)
- AM Air Powered motor with direct coupled oil pump
- AD Air Diaphragm powered pump.
- BT5 12Volt Battery Powered with 2 battery packs and 5GPM Pump.
- SP Special or Customized.
- 0 Water Removal Pre-Filter (Standard)
- 1 10 Micron Absolute Pre-Filter
- 2 3 Micron Absolute Pre-Filter
- 3 6 Micron Absolute Pre-Filter
- 4 Special
- 0 3 Micron Absolute Secondary Filter (Standard)
- 1 10 Micron Absolute Secondary Filter
- 2 6 Micron Absolute Secondary Filter
- 3 Water Removal Secondary Filter
- 4 Special
- OPTIONS:
- Blank = No Options
- 1 GFCI Outlet Plug
- 2 Digital Flow Meter/Totalizer
- 3 Water Condition Monitor
- 4 Particle Counter / Monitor
- 5 Special Paint Color
- 6 Oil Analysis Ports (upstream & downstream of filters)
- 9 Tool Box (Aluminum Diamond Plate, adds 17" to length)
- 10 Flow Meter (Standard with Variable Speed Drives)
- 11 Magnetic Filter Wrap on filters
- 13 Portable Oil Can Holder (Can hold one of each size oil cans 2, 5 & 10)

### Specs:

TEFC frame - 115VAC  
 1, 2.5, 5 or 10 GPM Pump  
 25 ft electric cord reel,  
 7 ft transfer hose, quick disconnects  
 7' suction, 7' discharge with quick disconnects  
 Clear Poly Tote ,  
 4-Wheeled Cart with drip tray,  
 Desiccant Breather, Adapter, Tote breather kit  
 Many ways to power the pump  
 (air, electric, even variable flow),  
 On/Off Switch



Units ship on pallets, fully assembled for use.  
 All electric units include a 25Ft electric cord  
 (with 3-prong with ground wire)  
 Carts are 24" Wide X 48" Long.  
 Height depends on tank selection (32-115 Gallons 42-57").

## Y2K Fluid Power

3500 North St. Paul Ave.,  
 Sioux Falls, SD 57104  
 888.925.8882  
 605.338.9982  
 www.y2kfluidpower.com



888.925.8882  
 www.y2kfluidpower.com