



A DIVISION OF DAKOTA FLUID POWER, INC.

GUARDIAN BREATHER

GUARDIAN Specifications:

Model	Height	Diameter	Mounting	Silica Gel	Maximum	Maximum Air Flow	Maximum Reservoir Fluid Flow	Type of Medium	Isolation Check Valve	Compound Indicating Gauge	Cartridge
G5S1N	9 in 22.3 cm	5.125 in	1" NPT	1.5 lbs 0.68 kg	9.2 fl oz 272 mL	25 cfm	187 gpm	Silica Gel	No	No	GRC5S
G5S1NC	9 in 22.3 cm	5.125 in	1" NPT	1.5 lbs 0.68 kg	9.2 fl oz 272 mL	25 cfm	187 gpm	Silica Gel	Yes	No	GRC5SC
G5S1NC	9 in 22.3 cm	5.125 in	1" NPT	1.5 lbs 0.68 kg	9.2 fl oz 272 mL	25 cfm	187 gpm	Silica Gel	No	Yes	GRC5S
G5S1NGC	9 in 22.3 cm	5.125 in	1" NPT	1.5 lbs 0.68 kg	9.2 fl oz 272 mL	25 cfm	187 gpm	Silica Gel	Yes	Yes	GRC5SC
G8S1N	12 in 30.5 cm	5.125 in	1" NPT	2.8 lbs 1.27 kg	17.2 fl oz 508.7 mL	25 cfm	187 gpm	Silica Gel	No	No	GRC8S
G8S1NC	12 in 30.5 cm	5.125 in	1" NPT	2.8 lbs 1.27 kg	17.2 fl oz 508.7 mL	25 cfm	187 gpm	Silica Gel	Yes	No	GRC8SC
G8S1NG	12 in 30.5 cm	5.125 in	1" NPT	2.8 lbs 1.27 kg	17.2 fl oz 508.7 mL	25 cfm	187 gpm	Silica Gel	No	Yes	GRC8S
G8S1NGC	12 in 30.5 cm	5.125 in	1" NPT	2.8 lbs 1.27 kg	17.2 fl oz 508.7 mL	25 cfm	187 gpm	Silica Gel	Yes	Yes	GRC8SC

Replacement Cartridges:

Model	Height	Diameter	Mounting	Silica Gel	Maximum	Maximum Air Flow	Maximum Reservoir Fluid Flow	Type of Medium	Isolation Check Valve	Compound Indicating Gauge	Cartridge
GRC5S	5 in	5 in	n/a	1.5 lbs 0.68 kg	9.2 fl oz 272 mL	n/a	n/a	Silica Gel	No	n/a	n/a
GRC5SC	5 in	5 in	n/a	1.5 lbs 0.68 kg	9.2 fl oz 272 mL	n/a	n/a	Silica Gel	Yes	n/a	n/a
GRC8S	8 in	5 in	n/a	2.8 lbs 1.27 kg	17.2 fl oz 508.7 mL	n/a	n/a	Silica Gel	No	n/a	n/a