

**EXAMPLE CONFIGURATION:**

HT	D5	25	10	5	SH	SQ	40R	2	--	S
Frame Style	Filter Head	Primary Filter	Secondary Filter	Power Source/Pump	Hoses	Hose Connections	Power Cord	Frame Color		Additional Options

**For other options not listed above or custom builds, contact Y2K at 888-925-8882 or sales@y2kfluidpower.com**

									--	
Frame Style	Filter Head	Primary Filter	Secondary Filter	Power Source/Pump	Hoses	Hose Connections	Power Cord	Frame Color		Additional Options

**FRAME STYLE**

DC	Drum Filter Cart
DT	Drum Topper ( <i>Uses the Y series head</i> )
FPA	Aluminum Diamond Plated, FilterPak ( <i>Single D series head</i> )
UFPA	Ultra-light, Aluminum Framed FilterPak ( <i>Single M series head</i> )
HT	Filter Cart
PU	Panel Unit
T3	30 Gallon, Steel Tote Cart
TH	Tandem Filter Cart
PT32	Platform Cart w/ 32 gal Poly Tank
PT3232	Platform Cart w/ 2 ea 32 gal Poly Tanks
PT71	Platform Cart w/ 71 gal Poly Tank
PT115	Platform Cart w/ 115 gal Poly Tank
ZC	Special Filter Cart Construction

**FILTER HEAD OPTION**

Y	Compact, Low Pressure, Aluminum Heads
D5	Medium Pressure, Cast Aluminum Heads
M	Low Pressure, Aluminum Heads
NF	No Heads
ZF	Special Heads

**PRIMARY FILTER ELEMENT (1ST STAGE)**

**Y Series Filters** (*Only used with the Drum Topper*)

3	3"x 8", 3 Micron Filter Element, β3=1000
5	3"x 8", 5 Micron Filter Element, β7=1000
7	3"x 8", 7 Micron Filter Element, β7=1000
12	3"x 8", 12 Micron Filter Element, β12=1000
22	3"x 8", 22 Micron Filter Element, β22=1000
WR	3"x 8", Water Removal Element
WR	3"x 5", Water Removal Element
NE	No Element

**M Series Filters** (*Only used with the M series Heads*)

3	5"x 10", 3 Micron Filter Element, β3=1000
6	5"x 10", 6 Micron Filter Element, β6=1000
10	5"x 10", 10 Micron Filter Element, β10=1000
25	5"x 10", 25 Micron Filter Element, β25=1000
WR	5"x 10", Water Removal Element
NE	No Element

**D Series Filters** (*Only used with the D series Heads*)

4	5"x 14", 4 Micron Filter Element, β4=2000
7	5"x 14", 7 Micron Filter Element, β7=2000
10	5"x 14", 10 Micron Filter Element, β10=1000
25	5"x 14", 25 Micron Filter Element, β25=2000
WR	5"x 14", Water Removal Element
NE	No Element

**SECONDARY FILTER ELEMENT (2ND STAGE)**

**Y Series Filters** (*Only used with the Drum Topper*)

3	3"x 8", 3 Micron Filter Element, β3=1000
5	3"x 8", 5 Micron Filter Element, β7=1000
7	3"x 8", 7 Micron Filter Element, β7=1000
12	3"x 8", 12 Micron Filter Element, β12=1000
22	3"x 8", 22 Micron Filter Element, β22=1000
WR	3"x 8", Water Removal Element
WR	3"x 5", Water Removal Element
NE	No Element

**M Series Filters** (*Only used with the M series Heads*)

3	5"x 10", 3 Micron Filter Element, β3=1000
6	5"x 10", 6 Micron Filter Element, β6=1000
10	5"x 10", 10 Micron Filter Element, β10=1000
25	5"x 10", 25 Micron Filter Element, β25=1000
WR	5"x 10", Water Removal Element
NE	No Element

**D Series Filters** (*Only used with the D series Heads*)

4	5"x 14", 4 Micron Filter Element, β4=2000
7	5"x 14", 7 Micron Filter Element, β7=2000
10	5"x 14", 10 Micron Filter Element, β10=1000
25	5"x 14", 25 Micron Filter Element, β25=2000
WR	5"x 14", Water Removal Element
NE	No Element

**POWER SOURCE/PUMP**

First select the power source required and then your desired pump. \*\* The 115v, 1HP option is standard and no power source select is needed.

NP	No Power Source
-	115v, 60Hz, 1HP**
C	115v, 60Hz, 1/2 HP
Q	115v, 60Hz, 1/4 HP ( <i>Only available on the FilterPak and Drum Topper Units</i> )
E	Explosion Proof ( <i>Available in 115v and 230v</i> )
T	Three Phase, 230/460v
M	Air Motor ( <i>Filter, Lubricator &amp; Regulator included</i> )
V	Variable Speed
ZP	Special Power Source
1	1 GPM
2	2 GPM
5	5 GPM
10	10 GPM
ZX	Special Pump Option

**HOSES**

NH	No Hoses
SH	7ft clear, PVC Hose (3/4" Suction & 1/2" Discharge)
SH1	7ft clear, PVC Hose (1' Suction & 3/4" Discharge)
WH	7ft Black Hydraulic Hose (3/4" Suction & 1/2" Discharge)
WH1	7ft Black Hydraulic Hose (1" Suction & 3/4" Discharge)
ZH	Special Hose Type and/or Length

**HOSE END CONNECTIONS**

CQ	CamLock Connectors
TE	Threaded Ends
SQ	3/4" & 1/2" ISO B Quick Disconnects w/ Steel Dust Plugs
SQ1	1" & 3/4" ISO B Quick Disconnects w/ Steel Dust Plugs
AQ	3/4" & 1/2" ISO A Quick Disconnects w/ Steel Dust Plugs
AQ1	1" & 3/4" ISO A Quick Disconnects w/ Steel Dust Plugs
FQ	3/4" & 1/2" Flush Face Quick Disconnects w/ Steel Dust Plugs
FQ1	1" & 3/4" Flush Face Quick Disconnects w/ Steel Dust Plugs
HW	Hose Wands
NQ	No Connections
ZQ	Special Connections

**ELECTRIC CORD**

NC	No Cord
4P	4ft Electric Cord
8P	8ft Electric Cord
40R	40ft Retractable Cord Reel
25C	25ft Electric Cord
ZW	Special Cord Type or Plug

**FRAME COLOR OPTIONS**

1	Blaze Orange
2	Red
3	Blue
4	Black
5	Yellow
6	Silver
7	Special Color

**OPTIONS**

A	High Oil Temperature Alarm
B	Manual Bypass Valve
D	Digital Flow Meter/Totalizer
E	Color Coded Delta P Gauge
F	Visual Flow Meter
L	Lift Lugs
MF	Magnetic Pre-Filter w/ Cleanable Rod
HE	Heat Exchanger (Air/Oil or Water/Oil)
N	Push Button Sample Ports
O	Standard Minimes Sample Ports
P	Inline Particle Counter
S	Y-Strainer (149 mesh)
T	On/Off Timer Control
W	Water Content Monitor ( <i>For use with the Particle Counter</i> )
Y	Yellow Light Filter Indicator
SR	Solid Rubber Tires
FF	No Flat, 13" Tires
Z	Special Features and/or other Options not listed